

**ebm-papst St. Georgen GmbH & Co. KG**

Hermann-Papst-Straße 1

78112 St. Georgen

Phone: +49 7724 81-0

Fax: +49 7724 81-1309

www.ebmpapst.com

info2@de.ebmpapst.com

Nominal data

Type	3956 L	
Nominal voltage	[VAC]	230
Frequency	[Hz]	50
Speed	[min ⁻¹]	1550
Power input	[W]	6,0
Min. ambient temperature	[°C]	-40
Max. ambient temperature	[°C]	80
Air flow	[m ³ /h]	31
Sound power level	[B]	3,8
Sound pressure level	[dB(A)]	24

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

Technical features

Dimensions	92 x 92 x 25 mm
General description	AC fan with internal rotor shaded-pole motor.
Connection line	2 flat plugs 2.8 x 0.5 mm. Housing with grounding lug for M4 screw
Direction of protection	Left, looking at rotor
Direction of air flow	Air exhaust over bars
Bearing	Ball bearings
Lifetime L10 at 40 °C	70000 h
Lifetime L10 at maximum temperature	27500 h
Mass	0.280 kg
Housing material	Metal
Material of impeller	Mineral-reinforced PA plastic
Motor protection	Protected from overload using impedance protection
Approval	VDE, CSA, UL, CE

AC axial compact fan

Technical drawing of a fan assembly showing dimensions for the fan frame and mounting plate. The drawing includes the following dimensions:

- Top left dimension: $25,4 \pm 0,3$
- Top right dimension: 4
- Bottom left dimension: $92 \pm 0,3$
- Bottom right dimension: $4,3 \pm 0,15$ (6x)
- Right side dimension: $4,5 \pm 0,2$
- Inner square frame dimension: $82,5 \pm 0,2$
- Outer square frame dimension: $82,5 \pm 0,2$
- Outer square frame dimension: 88
- Mounting hole diameter: $\varnothing 98$

Charts: Air flow

