

**ebm-papst St. Georgen GmbH & Co. KG**

Hermann-Papst-Straße 1

D-78112 St. Georgen

Phone: +49(0)7724/81-0

Fax: +49(0)7724/81-1309

info2@de.ebmpapst.com

www.ebmpapst.com

Nominal data

Type	8556 TV	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50
Speed	min ⁻¹	2750
Power input	W	12.0
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	90
Air flow	m ³ /h	40
Sound pressure level	dB(A)	28

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

Technical features

Dimensions	76 Ø x 37 mm
General description	AC fan with external rotor shaded-pole motor
Connection line	2 single strands AWG 18
Direction of rotation	Right, looking at rotor
Direction of air flow	Air exhaust over mounting bracket
Note	Flow rates and noise levels of fans without external housing depend on installation circumstances. The air flow stated here was determined with an orifice of 76.5 mm Ø and at a distance of approximately 17 mm from the mounting bracket. Under exceptionally favorable mounting conditions, the air flow of fan series 8000 A is achievable. The noise in the optimal operating range can only be measured for these fans in a specific application.
Bearing	Ball bearings
Lifetime L10 at 40 °C	52500 h
Lifetime L10 at maximum temperature	15000 h
Mass	0.370 kg
Material of impeller	Metal
Motor protection	Protected from overload using impedance protection
Approval	VDE, CSA, UL, CE

Product drawing

